

Certificate of constancy of performance



Number	0620-CPR-45875/06	Replaces	0620-CPR-45875/05
Issued	2017-02-01	First issued under CPR	2013-11-01
		First issued under CPD	2008-11-01

In compliance with Regulation 305/2011/EU of the European Parliament and of the Council of 9 March 2011 (the Construction Products Regulation or CPR), this certificate applies to the construction product

High-pressure decorative laminates (HPL)

whereby the scope of construction products is listed on page 2 of this certificate

produced by or for

GENTAŞ A.Ş.

and produced in the manufacturing plant

GENTAŞ GENEL METAL SANAYI VE TICARET A.Ş.

This certificate attests that all provisions concerning the assessment and verification of constancy of performance in Annex ZA of the standard

EN 438-7:2005

under system 1 for the performances set out in this certificate are applied and that the factory production control conducted by the manufacturer is assessed to ensure the constancy of performance of the construction product.

This certificate was first issued on 2008-11-01 and will remain valid as long as neither the harmonised standard, the construction product, the AVCP methods nor the manufacturing conditions in the plant are modified significantly, unless suspended or withdrawn by the notified product certification body.

Luc Leroy
Kiwa

Advise: consult www.kiwa.nl to check whether the certificate is valid.

**Notified Body No. 0620
Kiwa Nederland B.V.**

Sir Winston Churchillaan 273
Postbus 70
2280 AB RIJSWIJK
The Netherlands

Tel. +31 (0) 88 998 44 00
Fax +31 (0) 88 998 44 20
info@kiwa.nl
www.1kiwa.com

Manufacturer

GENTAŞ A.Ş.
Dolanti Sk No: 21
Sitelere 06610 Ankara
TURKEY
T +90.312 353 02 06
F +90.312 350 99 17
E gentas@gentas.com.tr
I www.gentas.com.tr

Manufacturing plant

GENTAŞ GENEL METAL SANAYI VE
TICARET A.Ş.
Serpek Mevkii 14841 Mengen/BOLU
TURKEY
T +90.374 356 18 78
F +90.374 356 11 60
E gentas@gentas.com.tr
I www.gentas.com.tr



Certificate of constancy of performance



0620-CPR-45875/06

High-pressure decorative laminates (HPL)

SCOPE

Interior and exterior grade Compact laminates with the reaction to fire classification **B-s1, d0**, with field of direct application:

- Compact high-pressure decorative laminate (HPL) panels for internal and external wall and ceiling finishes and
- Compact high-pressure decorative laminate (HPL) panels for internal and external suspended ceilings.

Interior grade

- G-Fire : ≥ 6 mm, CGF - Interior Compact General-purpose Flame-retardant grade
- G-BIO : ≥ 10 mm, CGF - Interior Compact General-purpose Flame-retardant grade
- ZERO PST : ≥ 10 mm, CGF - Interior Compact General-purpose Flame-retardant grade

Exterior grade

- G-Ext : ≥ 6 mm, EDF - Exterior Severe-use Flame-retardant grade
- G-Com UV⁺ : ≥ 6 mm, EDF - Exterior Severe-use Flame-retardant grade